

## Guilford of Maine

Fabric
To the Point

## TO THE POINT FABRIC

Fabric Card

While every effort is made to present as accurate reproduction as possible, colors on actual products may vary slightly from digital reproductions.



NOTE: We do not guarantee matches and recommend you examine a sample prior to excepting a color match.













## TO THE POINT FABRIC

Fabric Card

CDECIFICATIONS	
SPECIFICATIONS	4733
Style:	4732
Contents:	56% Polyester,
	44% Post-Consumer Recycled Polyester
Weight:	8.7 ± 0.5 oz./lin. yd.
Width:	54" min. useable
Backing:	Acrylic Backcoating
Treatment:	BLOCKaide®
Repeat:	None
Cleaning Code:	Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners
PERFORMANCE	
Abraison Resistance* ASTM D-4157	140,000 double rubs cotton duck
Pilling Resistance ASTM D-3511	Class 4 min.
Colourfastness to Light AATCC 16-A	Grade 4 min. at 40 hours
Colorfastness to Crocking AATCC 8	Grade 4 min. dry & Grade 3 min. wet

## **FLAMMABILITY**

CA Technical Bulletin 117-2013 Section 1











